



Part Number	IF-WFH3002
Dimensions	L - 4.0" x W - 4.0" x H - 1.25"
Software	V.0.0.25
Input Voltage	5VDC 50/60 Hz +/- 15%
Current Draw	100ma(standby)
Operating temperature	0-50c (32F to 122F)
Storage Temperature	0-65C (32F to 150F)
Start Up Scan Cycle	2 minutes
Bluetooth Broadcast Range	10m/30f (Line of Sight)
Communications Protocol	Bluetooth 4.0 LE / WiFi B/G/N 2.4ghz
Connection	USB Type C
Warranty	24 months RTB
Transmit Power 802.11b Average	+19dbm
Transmit Power 802.11n Average	+16dbm



WiFi | Bluetooth Hub




Dual Communication

Industry designed hub for safe and secure communication between smart bluetooth modules and remotes.



Plug n Play

Easy to setup!. Just plug it in and connect to your network and you are all set. Customizable command control for each OEM or distributor.



Data Diagnostics

Monitor usage, troubleshooting, models, serial numbers etc with optional data portal. Market directly to your customer with new products and features.



Industry Built

Control your smart modules and remote controls from anywhere around the world with the WiFi | Bluetooth Hub.



Cross Platform Compatibility

The WiFi Bluetooth hub works with all Flame- Flame-Tec and i-Flame smart products.



Voice Control

The WiFi Bluetooth hub works with Alexa and Google Home*.

Coming Soon.

